

## TESTREPORT EN926-2:2005

## UP ASCENT 3 M

**Type designation** UP Ascent 3 M  
**Type test reference no** DHV GS-01-2062-13  
**Holder of certification** [UP International GmbH](#)  
**Manufacturer** [UP International GmbH](#)  
**Classification** A  
**Winch towing** Yes  
**Number of seats min / max** 1 / 1  
**Accelerator** Yes  
**Trimmers** No



## BEHAVIOUR AT MIN WEIGHT IN FLIGHT (75KG)

## BEHAVIOUR AT MAX WEIGHT IN FLIGHT (120KG)

## Test pilots



Beni Stocker

No release



Sebastian Mackrodt

No release

## Inflation/take-off

A

A

**Rising behaviour** Smooth, easy and constant rising

Smooth, easy and constant rising

**Special take off technique required** No

No

## Landing

A

A

**Special landing technique required** No

No

## Speeds in straight flight

A

A

**Trim speed more than 30 km/h** Yes

Yes

**Speed range using the controls larger than 10 km/h** Yes

Yes

**Minimum speed** Less than 25 km/h

Less than 25 km/h

## Control movement

A

A

**Symmetric control pressure** Increasing

Increasing

**Symmetric control travel** Greater than 55 cm

Greater than 65 cm

## Pitch stability exiting accelerated flight

A

A

**Dive forward angle on exit** Dive forward less than 30°

Dive forward less than 30°

**Collapse occurs** No

No

## Pitch stability operating controls during accelerated flight

A

A

**Collapse occurs** No

No

## Roll stability and damping

A

A

**Oscillations** Reducing

Reducing

## Stability in gentle spirals

A

A

**Tendency to return to straight flight** Spontaneous exit

Spontaneous exit

## Behaviour in a steeply banked turn



A

A

**Sink rate after two turns** Up to 12 m/s

Up to 12 m/s

## Symmetric front collapse

A

A

**Entry** Rocking back less than 45°

Rocking back less than 45°

	<b>Recovery</b> Spontaneous in less than 3 s	Spontaneous in less than 3 s
	<b>Dive forward angle on exit</b> Dive forward 0° to 30°	Dive forward 0° to 30°
	<b>Change of course</b> Keeping course	Keeping course
	<b>Cascade occurs</b> No	No
<b>Symmetric front collapse in accelerated flight</b> <b>A</b>		
	<b>Entry</b> Rocking back less than 45°	Rocking back less than 45°
	<b>Recovery</b> Spontaneous in less than 3 s	Spontaneous in less than 3 s
	<b>Dive forward angle on exit</b> Dive forward 0° to 30°	Dive forward 0° to 30°
	<b>Change of course</b> Keeping course	Keeping course
	<b>Cascade occurs</b> No	No
<b>Exiting deep stall (parachutal stall)</b> <b>A</b>		
	<b>Deep stall achieved</b> Yes	Yes
	<b>Recovery</b> Spontaneous in less than 3 s	Spontaneous in less than 3 s
	<b>Dive forward angle on exit</b> Dive forward 0° to 30°	Dive forward 0° to 30°
	<b>Change of course</b> Changing course less than 45°	Changing course less than 45°
	<b>Cascade occurs</b> No	No
<b>High angle of attack recovery</b> <b>A</b>		
	<b>Recovery</b> Spontaneous in less than 3 s	Spontaneous in less than 3 s
	<b>Cascade occurs</b> No	No
<b>Recovery from a developed full stall</b> <b>A</b>		
	<b>Dive forward angle on exit</b> Dive forward 0° to 30°	Dive forward 0° to 30°
	<b>Collapse</b> No collapse	No collapse
	<b>Cascade occurs (other than collapses)</b> No	No
	<b>Rocking back</b> Less than 45°	Less than 45°
	<b>Line tension</b> Most lines tight	Most lines tight
<b>Asymmetric collapse 45-50%</b> <b>A</b>		
	<b>Change of course until re-inflation</b> Less than 90°	Less than 90°
	<b>Maximum dive forward or roll angle</b> Dive or roll angle 0° to 15°	Dive or roll angle 0° to 15°
	<b>Re-inflation behaviour</b> Spontaneous re-inflation	Spontaneous re-inflation
	<b>Total change of course</b> Less than 360°	Less than 360°
	<b>Collapse on the opposite side occurs</b> No	No
	<b>Twist occurs</b> No	No
	<b>Cascade occurs</b> No	No
<b>Asymmetric collapse 70-75%</b> <b>A</b>		
	<b>Change of course until re-inflation</b> Less than 90°	Less than 90°
	<b>Maximum dive forward or roll angle</b> Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
	<b>Re-inflation behaviour</b> Spontaneous re-inflation	Spontaneous re-inflation
	<b>Total change of course</b> Less than 360°	Less than 360°
	<b>Collapse on the opposite side occurs</b> No	No
	<b>Twist occurs</b> No	No
	<b>Cascade occurs</b> No	No
<b>Asymmetric collapse 45-50% in accelerated flight</b> <b>A</b>		
	<b>Change of course until re-inflation</b> Less than 90°	Less than 90°
	<b>Maximum dive forward or roll angle</b> Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
	<b>Re-inflation behaviour</b> Spontaneous re-inflation	Spontaneous re-inflation
	<b>Total change of course</b> Less than 360°	Less than 360°
	<b>Collapse on the opposite side occurs</b> No	No
	<b>Twist occurs</b> No	No
	<b>Cascade occurs</b> No	No
<b>Asymmetric collapse 70-75% in accelerated flight</b> <b>A</b>		
	<b>Change of course until re-inflation</b> Less than 90°	Less than 90°
	<b>Maximum dive forward or roll angle</b> Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°

<b>Re-inflation behaviour</b>	Spontaneous re-inflation	Spontaneous re-inflation
<b>Total change of course</b>	Less than 360°	Less than 360°
<b>Collapse on the opposite side occurs</b>	No	No
<b>Twist occurs</b>	No	No
<b>Cascade occurs</b>	No	No
<b>Directional control with a maintained asymmetric collapse</b>	<b>A</b>	<b>A</b>
<b>Able to keep course</b>	Yes	Yes
<b>180° turn away from the collapsed side possible in 10 s</b>	Yes	Yes
<b>Amount of control range between turn and stall or spin</b>	More than 50 % of the symmetric control travel	More than 50 % of the symmetric control travel
<b>Trim speed spin tendency</b>	<b>A</b>	<b>A</b>
<b>Spin occurs</b>	No	No
<b>Low speed spin tendency</b>	<b>A</b>	<b>A</b>
<b>Spin occurs</b>	No	No
<b>Recovery from a developed spin</b>	<b>A</b>	<b>A</b>
<b>Spin rotation angle after release</b>	Stops spinning in less than 90°	Stops spinning in less than 90°
<b>Cascade occurs</b>	No	No
<b>B-line stall</b>	<b>A</b>	<b>A</b>
<b>Change of course before release</b>	Changing course less than 45°	Changing course less than 45°
<b>Behaviour before release</b>	Remains stable with straight span	Remains stable with straight span
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Cascade occurs</b>	No	No
<b>Big ears</b>	<b>A</b>	<b>A</b>
<b>Entry procedure</b>	Dedicated controls	Dedicated controls
<b>Behaviour during big ears</b>	Stable flight	Stable flight
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Big ears in accelerated flight</b>	<b>A</b>	<b>A</b>
<b>Entry procedure</b>	Dedicated controls	Dedicated controls
<b>Behaviour during big ears</b>	Stable flight	Stable flight
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Behaviour immediately after releasing the accelerator while maintaining big ears</b>	Stable flight	Stable flight
<b>Behaviour exiting a steep spiral</b>	<b>A</b>	<b>A</b>
<b>Tendency to return to straight flight</b>	Spontaneous exit	Spontaneous exit
<b>Turn angle to recover normal flight</b>	Less than 720°, spontaneous recovery	Less than 720°, spontaneous recovery
<b>Sink rate when evaluating spiral stability</b>	14 [m/s]	14
<b>Alternative means of directional control</b>	<b>A</b>	<b>A</b>
<b>180° turn achievable in 20 s</b>	Yes	Yes
<b>Stall or spin occurs</b>	No	No
<b>Any other flight procedure and/or configuration described in the user's manual</b>		
No other flight procedure or configuration described in the user's manual		